

## H.265 & H.264 4K Video Display Via Mainstream 5 in 1 CCTV Tester with 7" Touch Screen Monitor Analog + IP + HD TVI CVI AHD Camera Tester with Network Cable Toner



7" Touch Screen 1920x1200 Resolution Multifunction Tester, H.265 decoding, 4K video display via mainstream HDMI signal Input, Analog + IP +HD-TVII/AHD/CVI Test, 12V2A/5V 2A Power Bank, PoE Power Output, HDMI Input & Output, Built-in WIFI, and Cable Toner for cable search.

### Features:

- 7" Touch Screen 1920x1200 Resolution
- H.265 & H.264, 4K video display via mainstream
- IP Camera Test by ONVIF, Support 2592x1520 Resolution
- 5MP TVI, 4MP AHD & CVI camera test, 4x zoom, video record and playback, coaxial PTZ control and call camera OSD menu.
- 12VDC 2A Power Output and 5VDC 2A USB Power Output, PoE Switch and PoE camera voltage and power test
- Audio Input & Output
- Enhanced UTP cable test and Cable Toner for cable search
- New-RJ45 TDR cable test. Test cable pair status, length, attenuation, impedance & skew.
- Digital Image Zoom on the Monitor, Video Screenshot, recording and playback
- DHCP Dynamic Address Assignment, Multiple Network IP Camera Test
- IP Address Scan, Ping Test, PoE Port Finder, PoE Voltage Test
- LED Flashlight
- Built-in WIFI
- HDMI Signal Input & output 1080p
- Integrated battery more energy efficiency.
- Backlight button for easy operation under dark environment.

## Specifications:

<b>Model</b>	<b>MX7HDATC-4K</b>
Monitor	7" Retina Touch screen 1920x1200 resolution
Video Mode	CVBS Input and looped output, NTSC/PAL auto adapt BNC Output color bar generator
	IPC test/IPC Viewer/Rapid video/RTSP/ONVIF
	5MP TVI camera test 2560x1944p 12.5fps 4MP CVI camera test 2560x1440p 25/30 fps 4MP AHD camera test 2560x1440p 15/25/30 fps
	HDMI input 1080p, 4K output
	Image 4x zoom, screen snapshot, record, save, view, recording & playback.
Power	12V/2A, 48V PoE & 5V/2A power output
Cable test	Cable tracer, UTP cable test, rj45 cable TDR test.
Tester Play	Screen projection: tester, android, version mobile phone & PC display at the same time
Network Test	Trace route, link monitor, DHCP server, port flashing, Ping test
WIFI	Built in WIFI, speeds 150M, display wireless camera image
Audio Test	Audio Input & Output
Data Monitor	Captures & analyzes the command data from controlling device, also can send hexadecimal
PoE Test	Measurement PoE switch or PSE power supply voltage and cable connection status
Drop-down menu	You can select PoE power switch, IP setting, WLAN switch, HDMI IN functions etc in any interface
External Power	DC12V 2A
Battery	Built-in 7.4V Lithium polymer battery, 5000mAh
Rechargeable	After charging 6-7 hours, normal working time 10 hours
Operation setting	OSD menu, select your desire language: English, Spanish, Italian, French, etc
Auto off	1-30 minutes
Working Temperature	-10 °C ---+50 °C
Working Humidity	30%-90%
Dimension/Weight	255x160x46 mm/0.95Kg

## Accessories:

